



GE Bright Stik™ LED 9/STIK/830/220-240V/E27/BX 93064019

Product information

LED Bright Stik™ illuminates spaces with light instantly. Its sleek cylindrical shape fits in place of a traditional incandescent bulb - and some sockets where a traditional bulb or CFL doesn't fit . Replace a 40W, 60W & 100W incandescent with an LED Bright Stik and keep saving for the next 15 years*. That's a long time you can spend not worrying about light bulbs.

Application areas





ਰ Home







Product data

Product Code	93064019
Bulb Shape	Т38
Bulb Finish	White
Bulb maximum overall diameter [mm]	38
Nominal Length [mm]	115.5
Net weight per piece [g]	42
RoHS compliant	Yes
Brand	GE BX
Cap/Base	E27

Performance data

Nominal beam angle [°]	240
Nominal Initial Lumens per Watt [lm/W]	90
Rated efficacy [lm/W]	90
Energy efficiency class (EEC)	A+
Rated life L70/B50 [h]	15000
Nominal correlated colour temperature (CCT) [K]]	3000
Nominal lumens [lm]	810
Colour Rendering Index (CRI) [Ra]	80





Electrical data

Nominal lamp power factor	>0.5
Operating Temperature (MIN) [°C]	-20°C
Operating Temperature (MAX) [°C]	+40°C
Startup time [sec]	<0.5s
Power Factor	>0.5
Number of switching cycles	50000
Dimming Capability	No
Nominal lamp voltage range [V]	220-240V
Nominal power [W]	9

Logistic data

DUN Code	10064894573894
EAN Code	0064894573897
Pack Quantity	15
Inner pack type	Box
Outer pack type	Carton
Product status	Available

Downloads & Links Go to the catalog site (HTTP) Product range datasheet (PDF) BrightStik range Datasheets (HTTP) BrightStik range images (HTTP) Lighting design tools & calculators (HTTP) Certificate for the Quality Management System of GE Lighting EMEA (PDF) Certificate for the Environmental Management System of GE Lighting EMEA (PDF)